

The new CNC generation.

Professional solutions for diverse industries.



Main specifications



Dimensions (W x L x H)

3540 x 2820 x 2450 mm



Weight (KG)

Approx. 1100 kg



Power Supply

Three-phase AC 380V 50/60Hz



Travel Speed

Up to 25m/min max.

R130

- Travel speed up to 25 m/min
- Tubular chassis, resistant to corrosion and stress
- Z axis, in aluminum with anti-corrosion treatment
- Work area: 1300 x 2500mm
- Height Z axis up to 200mm
- X/Y Axis: High precision helical rack and pinion
- Z axis: High precision auger
- 25mm linear guides
- 4.5kw air-cooled chuck
- Stepper motors
- RichAuto A11 DSP controller
- Vacuum table with 6 zones, electrically activated
- 7.5kw side channel vacuum pump with filter and safety valve
- 2.2kw industrial vacuum with bag
- Automatic lubrication system for linear guides
- "Mist Cooling" tool lubrication and cooling system
- Automatic tool sensor
- Vectric VCarve Pro software
- Connectivity: USB and Network

R130 ATC

- Travel speed up to 25 m/min
- Tubular chassis, resistant to corrosion and stress
- Z axis, in aluminum with anti-corrosion treatment
- Work area: 1300 x 2500mm
- Height Z axis up to 300mm
- X/Y Axis: High precision helical rack and pinion
- Z axis: High precision auger
- 25mm linear guides
- 7.5kw air-cooled chuck
- Automatic tool change with 4 units
- Hybrid servo motors with planetary gearboxes
- Embedded computer
- Vacuum table with 6 zones, electrically activated
- 7.5kw side channel vacuum pump with filter and safety valve
- 2.2kw industrial vacuum with bag
- Automatic lubrication system for linear guides
- "Mist Cooling" tool lubrication and cooling system
- Automatic tool sensor
- Vectric VCarve Pro software
- Connectivity: USB and Network

